

Norm. Gesloten / Fermée



Type	Description - Beschrijving	CEVAI
21HT3KOY110	3/8" DN-13 14 bar 90° NBR	ODE03215
21HT4KOY160	1/2" DN-16 14 bar 90° NBR	ODE03220
21HF5KOB200	3/4" DN-20 16 bar 90° NBR	ODE03225
21HF6KOB250	1" DN-25 16 bar 90° NBR	ODE03230
21HF7KOB350	5/4" DN-35 16 bar (DC=6 bar) 90° NBR	ODE03235
21HF8KOB400	6/4" DN-40 16 bar (DC=6 bar) 90° NBR	ODE03240
21W7KB500	2" DN-50 0,2...10 bar 90° NBR	ODE03245

21A2KV30	1/4" DN-3 10 bar 140° VITON	ODE03211
21HT3KOV110	3/8" DN-11 14 bar 140° VITON	ODE03180
21HT4KOV160	1/2" DN-16 14 bar 140° VITON	ODE03182
21HF5KOV200	3/4" DN-20 16 bar 140° VITON	ODE03184
21HF6KOV250	1" DN-25 16 bar 140° VITON	ODE03186

Norm. Open / Ouverte

21HT4ZOY160	1/2" DN-16 10 bar 90° NBR	ODE03320
21HT5ZOY160	3/4" DN-16 10 bar 90° NBR	ODE03325

3 weg / voies

31A2AV20	1/4" DN-2 10 bar 140° VITON	ODE03710
----------	-----------------------------	----------

Spoelen / Bobines

BDA	24 - 110 - 230 Volt AC & 12 Volt DC 8 Watt	ODE...
BVA	230 Volt 8 Watt IP67	ODE17220
GDV14230AY	230 Volt 14 Watt	ODE14230
GDV14024CY	24 Volt DC 14 Watt	ODE11024
R452971/60	voor/pour 21HT3/4/5 NO - 230 Volt	ODE03270
Connector spoel / Bobine - 3-pol. IP-65		ODE03170
Connector spoel / Bobine - 3-pol. IP-65 met/avec Diode		ODE03172



Ventiel voor water, mineraal olie, lucht, neutraal gas. Vanne pour eau, huile minérale, air, gaz neutre.

VE 174.4 FV 230V	1/8" DN-2,5 10 bar 140° VITON	PAR03140
------------------	-------------------------------	----------



Normalement ouverte

7321-BIN	3/8" DN-13 0,1...20 bar 90° NBR Coil 48...	PAR03215	ODE
7321-BAN	1/2" DN-13 0,1...20 bar 90° NBR Coil 48...	PAR03220	ODE
7321-BCN	3/4" DN-20 0,1...20 bar 90° NBR Coil 48...	PAR03225	ODE
7321-BCN-02 Slow	3/4" DN-20 0,1...10 bar 90° NBR Coil 48...	PAR03227	
7321-BDN	1" DN-25 0,1...20 bar 90° NBR Coil 48...	PAR03230	
7321-BDN-02 Slow	1" DN-25 0,1...10 bar 90° NBR Coil 48...	PAR03232	
7321-BEN	5/4" DN-35 0,1...10 bar 90° NBR Coil 48...	PAR03235	
7321-BFN	6/4" DN-40 0,1...10 bar 90° NBR Coil 48...	PAR03240	ODE
7321-BGN	2" DN-50 0,1...10 bar 90° NBR Coil 48...	PAR03245	ODE

7322-BAN	1/2" DN-13 0,1...20 bar 90° NBR Coil 48...	PAR03320	ODE
7322-BCN	3/4" DN-20 0,1...20 bar 90° NBR Coil 48...	PAR03325	ODE
7322-BDN	1" DN-25 0,1...20 bar 90° NBR Coil 48...	PAR03330	
7322-BEN	5/4" DN-35 0,1...10 bar 90° NBR Coil 48...	PAR03335	
7322-BFN	6/4" DN-40 0,1...10 bar 90° NBR Coil 48...	PAR03340	
7322-BGN	2" DN-50 0,1...10 bar 90° NBR Coil 48...	PAR03345	

3 weg / voies

PM 141 FV	1/4" DN-2 10 bar 140° VITON ZB09 or 12	PAR03710	ODE
-----------	--	----------	-----

Ventiel voor stoom en warm water. Vanne pour vapeur et eau chaude.

VE 161.4 AV 230V	1/8" DN-2,2 4 bar 140° VITON	PAR03405
7321-BIH	3/8" DN-13 0,1...4 bar 140° EPDM Coil 48...	PAR03415
7321-BAH	1/2" DN-13 0,1...4 bar 140° EPDM Coil 48...	PAR03420
7321-BCH	3/4" DN-20 0,1...4 bar 140° EPDM Coil 48...	PAR03425
7321-BDH	1" DN-25 0,1...4 bar 140° EPDM Coil 48...	PAR03430
7321-BEH	5/4" DN-35 0,1...4 bar 140° EPDM Coil 48...	PAR03435
7321-BFH	6/4" DN-40 0,1...4 bar 140° EPDM Coil 48...	PAR03440
7321-BGH	2" DN-50 0,1...4 bar 140° EPDM Coil 48...	PAR03445
PM 135 IT	3/8" DN-16 0,5...10 bar 180° TEFLON ZH14 or 16	PAR03290
PM 135 AT	1/2" DN-16 0,5...10 bar 180° TEFLON ZH14 or 16	PAR03292
PM 135 CT	3/4" DN-27 0,5...10 bar 180° TEFLON ZH14 or 16	PAR03294
PM 135 DT	1" DN-27 0,5...10 bar 180° TEFLON ZH14 or 16	PAR03296



Ventiel voor lichtestookolie  
Vanne pour fuel domestique



Type	Description - Beschrijving	CEVAI
VE 131 INX 230V	1/8" DN-1,7 25 bar 90° NBR	PAR03100 DELTA
VE 140 CRX 230V	1/4" DN-2,5 30 bar 140° RUBIN	PAR03120 RAPA
PM 153 BV	3/8" DN-5 5 bar 140° VITON ZB14 or 16	PAR03130 ODE
PM 153 GV	1/2" DN-5 5 bar 140° VITON ZB14 or 16	PAR03132
PM 123 IV	3/8" DN-13 5 bar 140° VITON ZB09 or 12	PAR03180 ODE
PM 123 AV	1/2" DN-13 5 bar 140° VITON ZB09 or 12	PAR03182 ODE
PM 123 CV	3/4" DN-20 3 bar 140° VITON JB14 or 16	PAR03184 ODE
PM 123 DV	1" DN-25 3 bar 140° VITON JB14 or 16	PAR03186
PM 120.4 AR OPEN	1/4" DN-3 30 bar 140° RUBIN ZH14	PAR03125

Ventiel voor gas EN-161  
Vanne pour gaz EN-161

VE 131.4 CG 230V	1/8" DN-4 2 bar 90° NBR	PAR03605
VE 131.4 GG 230V	1/4" DN-4 2 bar 90° NBR	PAR03610

Spoelen / Bobines



JB-14 IP-65	24 - 115 - 230 Volt / 50 Hz	PAR...
JB-16 IP-65	12 - 24 Volt DC	PAR...
YB-09 IP-67	24 - 230 Volt / 50 Hz	PAR...
ZB-09 IP-65	24 - 48 - 115 - 230 - 380 Volt / 50 Hz	PAR...
ZB-12 IP-65	12 - 24 Volt DC	PAR...
ZB-14 IP-65	24 - 115 - 230 - 380 Volt / 50 Hz	PAR...
ZB-16 IP-65	12 - 24 Volt DC	PAR...
ZH-14 IP-65	24 - 115 - 230 Volt / 50 Hz	PAR...
ZH-16 IP-65	24 Volt DC	PAR...
481865 IP-65	12 - 24 - 48 Volt DC - 380 Volt / 50 Hz	PAR...
483510 IP-65	230 Volt / 50 Hz	PAR...
483510 IP-65	24 - 48 - 115 Volt	PAR...

Spoelen / Bobines  
SERIE 7321 & 7322

115401 IP-54	Snoer/cordon 3 x 760 mm Spoel / Bobine Type X	PAR03150 DELTA
600003 IP-65	Connector spoel / Bobine Type JB / ZB / ZH / 732..	PAR03170 ODE
600040 IP-65	Connector spoel / Bobine Type WB	PAR03171

LET OP : spoel en ventiel worden afzonderlijk besteld, behalve voor ventiel type VE ( kraanhuis met spoel inbegr.)  
ATTENTION : bobine et vanne sont à commander séparément, sauf vanne type VE (corps avec bobine incluse)



Ventiel stookolie N.C.  
Vanne fuel N.C.



121-Z-2323 TUV	1/8" DN-2,2 33 bar 120° RUBIS 492425	LUC121Z2323
121-K-2423 TUV	1/8" DN-3 30 bar 160° RUBIS 483824	LUC121K2423
121-K-01	1/4" DN-5 7 bar 100° VITON 481865	LUC121K01
121-K-6423 TUV	1/4" DN-3 30 bar 160° RUBIS 483824	LUC121K6423
121-K-6220 TUV	1/4" DN-4 30 bar 160° RUBIS 483541	LUC121K6220
121-G-2320 TUV	3/8" DN-11 30 bar 160° VITON 483541	LUC121G2320
121-G-2523 TUV	1/2" DN-14 30 bar 160° VITON 483824	LUC121G2523
321-H-2322 TUV	3/8" DN-11 0,3...30 bar 160° VITON 483541	LUC321H2322
321-H-2522 / 23 TU	1/2" DN-15 0,3...30 bar 160° VITON 483541	LUC321H2523

Ventiel stookolie N.O.  
Vanne fuel N.O.

122-K-9321 TUV	1/8" DN-2,5 30 bar 160° RUBIS 483824	LUC122K9321
122-K-8321 TUV	1/4" DN-2,5 30 bar 160° RUBIS 483824	LUC122K8321
322-H-7306	3/8" DN-11 0,3...40 bar 140° VITON	LUC322H7306
322-H-7506	1/2" DN-14,5 0,3...40 bar 140° VITON	LUC322H7506

Ventiel - Vanne 3/2 - 5/2

341-L-9534	1/8" 1/4" DN-4 10 bar 75° NBR	LUC341L9534
341-L-9597	1/8" 1/4" DN-4 10 bar 75° NBR	LUC341L9597

Spoelen / Bobine LUCIFER

483541	115 - 230 Volt / 50 Hz 20 Watt	LUC...
483764 IP-65	115 - 230 Volt / 50 Hz 9 Watt DIN	LUC...
483824	115 - 230 Volt / 50 Hz 19 Watt	LUC...
492425	115 - 230 Volt / 50 Hz 14 Watt	LUC...
495910-N7 Eex	28 Volt DC	LUC495910